

Jonas Ihreborn AB
Expovägen 5
331 42 VÄRNAMO
SWEDEN

Testing of seating furniture according to EN 16139:2013 (3 appendices)

Customer:	Jonas Ihreborn AB
Test object/ID:	Stool/Polly
Test method:	EN 16139:2013 Furniture - Strength, durability and safety - Requirements for non-domestic seating. Test level 1
Scope:	Complete test
Date of test:	2017-12-01 – 2017-12-11
Test result:	The tested object passed the test
Reservation:	The test results in this report apply solely to the specimen tested
Test environment:	23 ± 2°C and 50 ± 5% relative humidity

RISE Research Institutes of Sweden AB **Building Technology - Wood Technological Assessment**

Performed by

Examined by

Robert Almqvist

Bengt-Åke Andersson

Appendices

1. Test result (3 pages)
2. Description of test object (1 page)
3. Pictures (2 pages)

RISE Research Institutes of Sweden AB

Postal address	Office location	Phone / Fax / E-mail
Box 857	Brinellgatan 4	+46 10 516 50 00
SE-501 15 BORÅS	SE-504 62 BORÅS	+46 33 13 55 02
Sweden		info@ri.se

This report may not be reproduced other than in full, except with the prior written approval of the issuing laboratory.

Appendix 1

Test result

Abbreviations: N/A = Not applicable
N/T = Not tested

Table 1

1.	Safety	EN 16139	Result
1.1	<p><u>General requirements</u></p> <p>The seating shall be so designed as to minimise the risk of injury to the user.</p> <p>All accessible parts shall be so designed that physical injury and damage are avoided.</p> <p>This requirement is met when:</p> <ul style="list-style-type: none"> a) accessible corners are rounded or chamfered; b) the edges of the seat, back rest and arm rests which are in contact with the user when sitting in the chair are rounded or chamfered; c) the edges of handles are rounded or chamfered in the direction of the force applied; d) all other edges are free from burrs and rounded or chamfered; e) the ends of hollow components are closed or capped. <p>Movable and adjustable parts shall be designed so that injuries and inadvertent operation are avoided.</p> <p>It shall not be possible for any load bearing part of the seating to come loose unintentionally.</p> <p>All parts which are lubricated to assist sliding shall be designed to protect users from lubricant stains when in normal use</p>	4.1	Pass
1.2	<p><u>Shear and squeeze points</u></p> <p>With the exception of tipping seats there shall be no shear and squeeze points created by parts of the seating operated by powered mechanisms, e.g. springs and gas lifts.</p> <p>There shall be no shear and squeeze points created by forces applied during normal use as well as during normal movements and actions</p> <p>Note!</p> <p>Shear and squeeze points that are created only during manually setting up and folding are acceptable, because the user can be assumed to be in control of his/her movements and to be able to cease applying the force immediately upon experiencing pain.</p>	4.2	Pass
1.3	<p><u>Rolling resistance of the unloaded chair</u></p> <p>≥ 12 N when tested in accordance with EN 1335-3:2009, 7.4; and all castors are of the same type</p>	4.4	N/A

Appendix 1

Table 2

2.	Stability	EN 1022	Result
2.1	Forwards overbalancing	6.2	Pass
2.2	Forwards overturning for seating with footrest	6.3	N/A
2.3	Sideways overbalancing, all seating without arms	6.4	Pass
2.4	Sideways overbalancing, all seating with arms	6.5	N/A
2.5	Rearwards overbalancing, all seating with backs	6.6	N/A

Table 3

3.	Strength, durability	Reference EN 1728	Cycles	EN 16139 level 1	Result
3.1	Seat and back static load test	6.4	10	Seat: 1600 N Back: 560 N	Pass N/A
3.2	Seat front edge static load test	6.5	10	1300 N	Pass
3.3	Vertical static load on back rests	6.6	10	600 N Seat: 1300 N	N/A
3.4	Foot rest and leg rest static load test	6.8 and 6.9	10	1300 N	N/A
3.5	Arm sideways static load test	6.10	10	400 N	N/A
3.6	Arm downwards static load test	6.11	5	750 N	N/A
3.7	Vertical upwards static load on arm rests for stackable seating	6.13.2	10	250 N	N/A
3.7 Annex B	Vertical upwards static load on arm rests for seating which may be moved when occupied	6.13.1	10	1200 N	N/A

Appendix 1

3.	Strength, durability	Reference EN 1728	Cycles	EN 16139 level 1	Result
3.8	Seat and back durability test	6.17	100 000	Seat: 1000N Back: 300 N	Pass N/A
3.9	Seat front edge durability test	6.18	50 000	800 N	Pass
3.10	Arm durability test	6.20	30 000	400 N	N/A
3.11	Foot rest durability test	6.21	50 000	1000 N	N/A
3.12	Leg forward static load test	6.15	10	500 N Seat: 1000 N	Pass
3.13	Leg sideways static load test	6.16	10	400 N Seat: 1000 N	Pass
3.14	Vertical seat impact test	6.24	10x2	240 mm	Pass
3.15	Horizontal seat impact test	6.25	10	210 mm/38°	Pass
3.16	Arm impact test	6.26	10	210 mm/38°	N/A
3.17	Auxiliary writing surface static load test	6.14	10	300 N	N/A
3.18	Auxiliary writing surface durability test	6.22	10 000	150 N	N/A

Appendix 2

Description of test Object

Test object/ID Stool/Polly

Dimensions

Width: 60 cm

Depth: 40 cm

Height: 43 cm

Mass: 4.3 kg

Components

Seat/frame: Plywood with flexible foam

Feet: Plastic

Upholstery: Fabric

Sampling: The test object was selected by the customer

Date of arrival at
RISE test laboratory: 2017-10-13

Observed defects before testing: No defects

Appendix 3

Pictures



Figure 1



Figure 2

Appendix 3



Figure 3



Figure 4